



## INTEL® STRATIX® 10 TX PRODUCT TABLE

PRODUCT LINE		TX 400	TX 850	TX 850	TX 1100	TX 1100	TX 1650	TX 2100	TX 2500	TX 2500	TX 2800	TX 2800	
Resources	Logic elements (LEs) <sup>1</sup>	378,000	841,000	841,000	1,325,000	1,325,000	1,679,000	2,073,000	2,422,000	2,422,000	2,753,000	2,753,000	
	Adaptive logic modules (ALMs)	128,160	284,960	284,960	449,280	449,280	569,200	702,720	821,150	821,150	933,120	933,120	
	ALM registers	512,640	1,139,840	1,139,840	1,797,120	1,797,120	2,276,800	2,810,880	3,284,600	3,284,600	3,732,480	3,732,480	
	Hyper-Registers from Intel® Hyperflex™ FPGA architecture	Millions of Hyper-Registers distributed throughout the monolithic FPGA fabric											
	Programmable clock trees synthesizable	Hundreds of synthesizable clock trees											
	eSRAM memory blocks	–	–	–	–	–	2	2	–	–	–	–	–
	eSRAM memory size (Mb)	–	–	–	–	–	94.5	94.5	–	–	–	–	–
	M20K memory blocks	1,537	3,477	3,477	5,461	5,461	6,162	6,847	9,963	9,963	11,721	11,721	
	M20K memory size (Mb)	30	68	68	107	107	120	134	195	195	229	229	
	MLAB memory size (Mb)	2	4	4	7	7	9	11	13	13	15	15	
	Variable-precision digital signal processing (DSP) blocks	648	2,016	2,016	2,592	2,592	3,326	3,960	5,011	5,011	5,760	5,760	
	18 x 19 multipliers	1,296	4,032	4,032	5,184	5,184	6,652	7,920	10,022	10,022	11,520	11,520	
	Peak fixed-point performance (TMACS) <sup>2</sup>	2.6	8.1	8.1	10.4	10.4	13.3	15.8	20.0	20.0	23.0	23.0	
	Peak floating-point performance (TFLOPS) <sup>3</sup>	1.0	3.2	3.2	4.1	4.1	5.3	6.3	8.0	8.0	9.2	9.2	
I/O and Architectural Features	Secure device manager	AES-256/SHA-256 bitstream encryption/authentication, physically unclonable function (PUF), ECDSA 256/384 boot code authentication, side channel attack protection											
	Hard processor system <sup>4</sup>	Quad-core 64-bit ARM® Cortex®-A53 up to 1.5 GHz with 32KB I/D cache, NEON coprocessor, 1 MB L2 Cache, direct memory access (DMA), system memory management unit, cache coherency unit, hard memory controllers, USB 2.0 x2, 1G EMAC x3, UART x2, SPI x4, I2C x5, general purpose timers x7, watchdog timer x4											
	Maximum user I/O pins	Yes	Yes	Yes	Yes	Yes	–	–	Yes	Yes	Yes	Yes	
	Maximum LVDS pairs 1.6 Gbps (RX or TX)	384	440	440	440	440	440	440	440	296	440	296	
	Total full duplex transceiver count	192	216	216	216	216	216	216	216	144	216	144	
	GXE transceiver count - PAM4 (up to 57.8 Gbps) or NRZ (up to 28.9 Gbps)	24	48	72	48	72	96	96	96	144	96	144	
	GXT transceiver count - NRZ (up to 28.3 Gbps)	12 PAM-4 24 NRZ	12 PAM-4 24 NRZ	24 PAM-4 48 NRZ	12 PAM-4 24 NRZ	24 PAM-4 48 NRZ	36 PAM-4 72 NRZ	36 PAM-4 72 NRZ	36 PAM-4 72 NRZ	60 PAM-4 120 NRZ	36 PAM-4 72 NRZ	60 PAM-4 120 NRZ	
	GX transceiver count - NRZ (up to 17.4 Gbps)	0	16	16	16	16	16	16	16	16	16	16	
	PCI Express® (PCIe®) hard intellectual property (IP) blocks (Gen3 x16)	0	8	8	8	8	8	8	8	8	8	8	
	100G Ethernet MAC (no FEC) hard IP blocks	0	1	1	1	1	1	1	1	1	1	1	
	100G Ethernet MAC + FEC hard IP blocks	0	1	1	1	1	1	1	1	1	1	1	
	Memory devices supported	4	4	8	4	8	12	12	12	20	12	20	
	DDR4, DDR3, DDR2, DDR, QDR II, QDR II+, RLDRAM II, RLDRAM 3, HMC, MoSys												
	Package Options and I/O Pins: General-Purpose I/O (GPIO) Count, High-Voltage I/O Count, LVDS Pairs, E-Tile Transceiver Count and H-Tile Transceiver Count <sup>5,6</sup>												
F1152 pin (35mm x 35mm, 1.0mm pitch)	384,0,192,24,0												
F1760 pin (42.5 mm x 42.5 mm, 1.0 mm pitch)		440,8,216,24,24	–	440,8,216,24,24	–	–	–	–	–	–	–	–	
F2397 pin (50 mm x 50 mm, 1.0 mm pitch)	–	–	440,8,216,48,24	–	440,8,216,48,24	440,8,216,72,24	440,8,216,72,24	440,8,216,72,24	440,8,216,72,24	–	440,8,216,72,24	–	
F2912 pin (55 mm x 55 mm, 1.0 mm pitch)	–	–	–	–	–	–	–	–	–	296,8,144,120,24	–	296,8,144,120,24	

**Notes:**

- LE counts valid in comparing across Intel FPGA devices, and are conservative vs. competing FPGAs.
- Fixed point performance assumes the use of pre-adder.
- Floating point performance is IEEE-754 compliant single-precision.
- Quad-core ARM Cortex-A53 hard processor system present in select Stratix 10 TX devices.
- A subset of pins for each package are used for high-voltage 3.0 V and 2.5 V interfaces.
- All data is preliminary and subject to change without prior notice.

296,8,144,120,24 Numbers indicate total GPIO count, high-voltage I/O count, LVDS pairs, GXE (E-Tile) transceiver count, and GXT+GX (H-Tile) transceiver count

Indicates pin migration path.



## INTEL STRATIX 10 TX PRODUCT TABLE

PRODUCT LINE	TX 400	TX 850	TX 1100	TX 2500	TX 2800
Processor	Quad-core 64 bit ARM Cortex-A53 MPCore* processor				
Maximum processor frequency	1.5 GHz <sup>1</sup>				
Processor cache and co-processors	<ul style="list-style-type: none"> <li>• L1 instruction cache (32 KB)</li> <li>• L1 data cache (32 KB) with error correction code (ECC)</li> <li>• Level 2 cache (1 MB) with ECC</li> <li>• Floating-point unit (FPU) single and double precision</li> <li>• ARM NEON media engine</li> <li>• ARM CoreSight* debug and trace technology</li> <li>• System Memory Management Unit (SMMU)</li> <li>• Cache Coherency Unit (CCU)</li> </ul>				
Scratch pad RAM	256 KB				
HPS DDR memory	DDR4, DDR3 (Up to 64 bit with ECC)				
Direct memory access (DMA) controller	8 channels				
EMAC	3X 10/100/1000 Ethernet media access controller (EMAC) with integrated DMA				
USB on-the-go (OTG) controller	2X USB OTG with integrated DMA				
UART controller	2X UART 16550 compatible				
Serial peripheral interface (SPI) controller	4X SPI				
I <sup>2</sup> C controller	5X I <sup>2</sup> C				
Quad SPI flash controller	1X SIO, DIO, QIO SPI flash supported				
SD/SDIO/MMC controller	1X eMMC 4.5 with DMA and CE-ATA support				
NAND flash controller	<ul style="list-style-type: none"> <li>• 1X ONFI 1.0 or later</li> <li>• 8 and 16 bit support</li> </ul>				
General-purpose timers	4X				
Software-programmable general-purpose I/Os (GPIOs)	Maximum 48 GPIOs				
HPS DDR Shared I/O	3X 48 - May be assigned to HPS for HPS DDR access				
Direct I/Os	48 I/Os to connect HPS peripherals directly to I/O				
Watchdog timers	4X				
Security	Secure device manager, Advanced Encryption Standard (AES) AES-256/SHA-256 bitsream encryption/authentication, PUF, ECDSA 256/384 boot code authentication, side channel attack protection				

Notes:

1. With overdrive feature.